

## **Glutolin BW Wallpaper and Border Adhesive**

Ready to use, solvent-free emulsion based adhesive for heavyweight wall coverings, textile wallpapers and borders.

Instructions for use:	For pasting textile wall coverings, woven fabric wallpapers, glass cloth, PVC foils with woven backings as well as for use as a wallpaper adhesive additive	
Technical specifications:	Components:	Polyvinyl acetate ethylene emulsion
	pH-value:	approx. 9
	Density:	approx. 1.03 g/cm <sup>3</sup>
	Usage:	200-300 g/m <sup>2</sup>
Surface preparation:	The surface must be dry, firm, dust and free of release agents (dust, grease, etc.) Remove all old, loose wallpapers and distempers using <i>Glutosolv TA Wallpaper Remover</i> . Make good cracks and holes using <i>Glutofill WF Filler</i> or <i>Glutofill WG Super Bonding interior</i> . Pre-treat highly absorbent, sanding and chalking surfaces with <i>Glutogrund LF Deeply Penetrating Primer</i> .	
Application:	<ul> <li><u>As a wall covering adhesive:</u> Evenly apply <i>Glutolin BW Wallpaper and Border</i> <i>Adhesive</i> to the surface over a width equal to the width of the wall covering using a roller or brush and place the wall covering, cut to size, in the moist adhesive bed. If the adhesive is to be applied directly to the wall covering, observe the prescribed softening time.</li> <li>Always observe the wall covering manufacturer's pasting guidelines!</li> <li><u>As a border adhesive:</u> Moisten the borders with water and then apply a thin, uniform coat of <i>Glutolin BW Wallpaper and Border Adhesive</i> to the border. Fold the pasted ends of the borders together, roll up and leave to soften. After the prescribed softening time place the border on the surface and uniformly press into place.</li> <li>Always observe the border manufacturer's instructions for use!</li> <li><u>As an additive for wallpaper adhesive:</u> <i>Glutolin BW Wallpaper and Border</i> <i>Adhesive</i> can be used to increase the adhesive strength and moisture resistance of wallpaper adhesives. Thoroughly stir <i>Glutolin BW Wallpaper and</i> <i>Border Adhesive</i> into the already dissolved wallpaper adhesive. The optimum amount to be added is approx. 15-20 % e.g. a 750-g tin of <i>Glutolin BW</i> <i>Wallpaper and Border Adhesive</i> to 4 I stirred wallpaper adhesive.</li> </ul>	
		ual adhesive using a damp cloth. nd/or room temperature are below + 5° Celsius! Ise.
Storage:	Store in a cool place! Keep containers tightly sealed! The adhesive is frost- resistant. If frozen, defrost in room temperature and stir before use.	
Important information:	Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)	
Available sizes:	Can 750 g Art. no. 064541074 Tub 3 kg Art. no. 064552074 Tub 5 kg Art. no. 064543074 Tub 10 kg Art. no. 064544074 Tub 18 kg Art. no. 064545074	