

Glutolin M22 instant

High quality, readily soluble wallpaper adhesive of methylcellulose and synthetic resin - for wallpapering machines

Instructions for use: *Glutolin M22 instant* is ideally suited for the safe hanging of vinyl and embossed vinyl wallpapers, woodchip wallpapers, embossed wallpapers, heavy wallpapers, fabric wallpapers and other wallpapers coverings. Ideally set for the working with customary papering machines.

Technical specifications:

Components:	Methylcellulose, synthetic resin powder
Density:	0,55 g/cm ³
pH-value:	approx. 8
Solubility:	ready for use in about 5 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm and free of release agents (dust, formwork oil, etc.). Remove old peeling wallpaper and distemper using *Glutosolv TA wallpaper remover*. Tidy up cracks, and holes with *Glutofill WF filler interior* or *Glutofill WG Super Bonding Filler*. Pre-treat strongly absorbent, abrasive and chalky surfaces with *Glutogrund Deeply Penetrating Primer LF*.

Water soluble contamination of the surface to which the wallpaper is to be applied which may bleed through during papering should be isolated using a *sealer spray*. To make subsequent removal easier, it is recommended, for washable wallpapers in particular, that the surface to which the wallpaper is to be applied be treated with *wallpaper sizing*.

Application: Add *Glutolin M22i* to cold and clear water (see table), stirring vigorously and continue to stir briefly. After about 5 minutes, stir vigorously once more. Apply the wallpaper adhesive with the papering machine or with the brush to the wallpaper, fold the cut strip of wallpaper and hang it after a sufficient curing period. Always follow the wallpaper and papering machines manufacturer's instructions. To improve moisture resistance or for slightly absorbent surfaces is the addition of 20 % *Glutolin BW Wallpaper and border adhesive* recommended. Do not use if the temperature of the room or object to which the wallpaper is to be applied is less than 5°C. Clean tools with water immediately after use.

Mixing ratio:

for	Mix	Amount of water per 300 g pack	300 g pack covers
Prepaste	1 : 40	12 l	approx. 100 - 120 m ²
Woodchip wallpapers, non-woven wallpapers, embossed vinyl wallpapers, as well as other heavy wallcoverings	1 : 20	6 l	approx. 30 m ²

Storage: Store in a cool dry place.

Important information: Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

Available sizes:
 300 g box Art. No. 063201074
 750 g box Art. No. 063202074