

Glutolin GTV

High-quality, quick-soluble methyl cellulose paste

Instructions for use:

Glutolin GTV is ideally suited for pasting non woven wallpaper by the new wallpapering technique or traditional wallpapering as well as for pasting woodchip, vinyl and embossed wallpapers.

Technical specifications:

Components: Methyl cellulose, polyvinyl acetate powder
 Density: Approx. 0.5 g/cm³
 pH-value: Approx. 8
 Solubility: Ready for use in approx. 5 minutes
 Usage: Approx. 200 - 300 ml/m²

Surface preparation:

The surface must be dry, stable and free of dust, grease etc. Remove old, peeling wallpaper and paint using *Glutosolv TA wallpaper remover*. Tidy up cracks, holes and uneven areas with *Glutofill WF filler* or *Glutofill WG super bonding filler*. Pre-treat strongly absorbent, abrasive and chalky surfaces with *Glutogrund LF Deeply Penetrating Primer*.

Application:

Add *Glutolin GTV* to cold, clean water, fast and stirring vigorously and continue to stir for a short time and resume after 3 minutes.

Application to surface: For the modern wallpapering technique – e.g. for pasting form-stable non woven wallpaper and many others – wallpaper manufacturers recommend pasting the surface. Apply the stirred *Glutolin GTV* for 1 to 2 strips of wallpaper evenly to the surface with a lambs wool roll. Lay strip of wallpaper on the fresh bed of paste and press on evenly.

Application to wallpaper: Paste wallpaper evenly with *Glutolin GTV* and fold over. After sufficient softening, apply on impact and press on. To enhance absorbency and for low-absorbent surfaces we recommend adding a 750 g tin *Glutolin BW Wallpaper and Border Adhesive* per stirred *Glutolin GTV* pack, but not if pasting dry-removable non woven wallpaper as then easy removal may be impaired.

Wallpaper manufacturers' instructions have to be followed. In case of paste remains on wallpaper front, remove with a wet cloth immediately.

Clean tools with warm or cold water.

Not to be used if the object and/or room temperature is below +5° Celsius.

Mixing ratio:

For	Ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1:40	8 l	60-80 m ²
Application to surface * non woven wallpaper * glass fibre wallpaper - laminated	1:15	3 l	15-20 m ²
Application to wallpaper: * Vinyl wallpaper * Fabric/textile wallpaper * Heavy wallpaper	1:20	4 l	20-25 m ²

Storage:

Store in a cool, dry place!

Important information:

Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

Available size:

Folding carton of 200 g Art. no. 063901074