

Glutolin V instant – Special Wallpaper Paste High-quality, quick-soluble methyl cellulose paste

Instructions for use:	<i>Glutolin V</i> is ideally suited for pasting non woven wallpaper by the new wallpapering technique or traditional wallpapering as well as for pasting woodchip, vinyl and embossed wallpapers.			
Technical specifications:	Components::	Methyl cell	ulose, polyvinyl acetate	e powder
	Density:	Approx. 0.4	15 g/cm³	
	pH-value:	Approx. 8		
	Solubility:	Ready for u	use in approx. 20 minu	tes
	Usage:	Approx. 20	0 ml/m²	
Surface preparation:	The surface must by dry, stable and free of dust, grease etc. Remove old, peeling wallpaper and paint using <i>Glutosolv TA Wallpaper Remover</i> . Tidy up cracks, holes and uneven areas with <i>Glutofill WF filler</i> or <i>Glutofill WG super bonding filler</i> . Pre-treat strongly absorbent, abrasive and chalky surfaces with <i>Glutogrund LF Deeply Penetrating Primer</i> .			
Application:	Add <i>Glutolin V</i> to cold, clean water, fast and stirring vigorously and continue to stir for a short time and resume after 3 minutes.			
	Application to surface: For the modern wallpapering technique – e.g. for pasting form-stable non woven wallpaper and many others – wallpaper manufacturers recommend pasting the surface. Apply the stirred <i>Glutolin V instant</i> for 1 to 2 strips of wallpaper evenly to the surface with a lambs wool roll. Lay strip of wallpaper on the fresh bed of paste and press on evenly.			
	Application to wallpaper: Paste wallpaper evenly with <i>Glutolin V instant</i> and fold over. After sufficient softening, apply on impact and press on. To enhance absorbency and for low-absorbent surfaces we recommend adding a 750 g tin <i>Glutolin BW Wallpaper and Border</i> Adhesive per stirred <i>Glutolin V instant</i> pack, but not if pasting dry-removable non woven wallpaper as then easy removal may be impaired.			
	Wallpaper manufacturers' instructions have to be followed. In case of paste remains on wallpaper front, remove with a wet cloth immediately.			
	Clean tools with warm or cold water.			
Mixing ratio:	For	Ratio	Amount of water per 200 g pack	200 g pack covers
	Prepaste	1:40	81	60-80 m ²
	Woodchip wallpapers, vinyl wallpapers and embossed wallpapers	1:25	51	25-30 m²
	Vinyl wallpapers	1:20	41	16-20 m²
Storage:	Store in a cool, dry place!			
Important information:	Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)			
Available size:	Folding carton of 200 g Art. No. 063101074			