

# Glutolin GTX special adhesive

High quality, universal use wallpaper adhesive with methylcellulose

**Instructions for use:** For hanging vinyl and blown vinyl wallpaper, all types of fabric wallpaper, glass fibre wall coverings, paper backed glass fibre wall coverings and all heavy wallpapers. Cement and chalk resistant.

**Technical specifications:**

Components::	Methylcellulose, dispersing agent, starch ether.
Density:	0.50 g/cm <sup>3</sup>
pH-value:	approx. 8
Solubility	ready for use in about 30 minutes
Usage:	200-300 ml/m <sup>2</sup>

**Surface preparation:** The surface to which the wallpaper is to be applied must be dry, stable and free of dust and grease. Remove old peeling wallpaper and distemper using *Glutosolv TA wallpaper remover*. Tidy up cracks, and holes with *Glutofill WF filler* or *Glutofill WG super bonding filler*. Pre-treat strongly absorbent, abrasive and chalky surfaces with *Glutogrund Deeply Penetrating Primer*. Water soluble contamination of the surface to which the wallpaper is to be applied which may bleed through during papering should be isolated using a *sealer spray*.

For very translucent wallpaper and contrasting backgrounds, we recommend applying a coat of *Glutogrund TP Wallpaper Primer* beforehand. To make subsequent removal easier, it is recommended, for washable wallpapers in particular, that the surface to which the wallpaper is to be applied be treated with *wallpaper sizing*.

**Application:** Add *Glutolin GTX* to cold water, stirring vigorously and continue to stir briefly. After about 30 minutes, stir vigorously once more.

**If applying to the wallpaper:**

Apply evenly, fold and allow to cure. After an appropriate curing period, hang wallpaper flush in the usual manner and smooth using a seam roller.

**If applying to the surface to which the wallpaper is to be applied:**

To avoid bubble formation, lightly moisten the back of the cut strip of wallpaper about 5 minutes before hanging. Apply *Glutolin GTX* evenly using a sheepskin roller to a width of 1-2 sheets of wallpaper. Apply wallpaper to the paste treated area and press into place. After a short wait, smooth the seam between sheets with a smooth seam roller. To improve moisture resistance or for slightly absorbent surfaces, the addition of 20 % *Glutolin BW wall and border adhesive* (750 g bucket) is recommended.

Always follow the wallpaper manufacturer's instructions.

Wipe off excess paste on the front of the wallpaper with water immediately.

Do not use if the temperature of the room or surface to which the wallpaper is to be applied is less than 5°C.

Clean tools with water immediately after use.

**Mixing ratio:**

for	Mix	Amount of water per 500g pack	500g pack covers
Blown vinyl wallpaper, embossed non-woven wall coverings, glass fibre fabrics, fabric wallpapers	1:15	7.5	37-45 m <sup>2</sup>

**Storage:** Store in a cool dry place. Ensure that the container is properly closed.

**Important information:** Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

**Available sizes:** Carton 200g Art. No. 062301074