

Glutolin M- Paste for wallpapering machines

Quickly soluble wallpaper adhesive of methylcellulose and synthetic resin - for wallpapering machines

Instructions for use:

Glutolin M is ideally suited for the safe hanging of vinyl and embossed vinyl wallpapers, woodchip wallpapers, embossed wallpapers, heavy wallpapers, textile wallpapers and other wallpapers coverings. Ideally set for the working with customary papering machines.

Technical specifications:

Components: Methylcellulose, synthetic resin powder
 Density: 0,5 g/cm³
 pH-value: 7-8
 Solubility: ready for use in 10 minutes
 Usage: approx. 200 ml/m²

Surface preparation:

The surface must be dry, stable and free of dust, grease etc. Remove old, peeling wallpaper and paint using *Glutosolv TA wallpaper remover*. Tidy up cracks, holes and uneven areas with *Glutofill WF filler* or *Glutofill WG super bonding filler*. Pre-treat strongly absorbent, abrasive and chalky surfaces with *Glutogrund LF Deeply Penetrating Primer*.

Water soluble contamination of the surface which may bleed through during papering should be isolated using a *sealer spray*. To make subsequent removal easier, it is recommended, for washable wallpapers in particular, that the surface to which the wallpaper is to be applied be treated with *wallpaper sizing*.

Application:

Add *Glutolin M* to cold and clear water (see table), stirring vigorously and continue to stir briefly. After 10 minutes stir vigorously once more.

Apply the wallpaper adhesive with the papering machine or with the brush to the wallpaper, fold the cut strip of wallpaper and hang it after a sufficient curing period.

Always follow the wallpaper and papering machines manufacturer's instructions.

To improve moisture resistance or for slightly absorbent surfaces is the addition of a 750 g tin *Glutolin BW Wallpaper and border adhesive* per 200 g pack *Glutolin M* recommended.

Do not use if the temperature of the room or object to which the wallpaper is to be applied is less than 5°C.

Clean tools with water after use.

Mixing ratio:

for	Mix	Amount of water per 500 g pack	500 g pack covers
Prepaste	1 : 70	35 l	220 - 350 m ²
Embossed wallpapers, woodchip wallpapers, low weight wallpapers	1 : 35	17,5 l	75 - 90 m ²

Storage:

Store in a cool dry place.

Important information:

Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

Available sizes:

Box 200g Art. No. 062501074
 Box 500g Art. No. 062522074