

## Glutolin TA Wallpaper Remover

Quickly and easily removes all types of wallpapers and woodchip.

**Area of application:**

*Glutolin TA* is suitable for fast and easy removal of coated woodchip wallpaper, plastic coated and wash resistant wallpaper such as textile, vinyl and paper wallpaper.

- highly effective concentrate
- accelerates the soaking of wallpaper
- high coverage
- contains biodegradable surfactants
- free of solvents
- odourless

**Technical specifications:**

Components:	Nonionic surfactants, water, additives
Density:	approx. 1.0 g/cm <sup>3</sup>
pH-value:	approx. 7-8
Consumption:	250 ml for up to 100 m <sup>2</sup> depending on dilution

**Instructions:**

Add 250 ml *Glutolin TA* Wallpaper Remover into 5 l of water and mix.

Double the amount of water for light-weight wallpaper. Apply the liquid evenly and generously and leave to soak for 10-20 minutes. For heavy and wash resistant wallpaper apply twice if necessary. Treat waterproofed coatings and coated wallpapers with a spiked roller or roughen up with a coarse sandpaper to ease the penetration of the liquid. Then peel off the soaked wallpaper.

Cover moisture-sensitive surfaces (floors, doors).

Clean tools with water. For the application of new wallpaper we recommend Glutolin Wallpaper Adhesive.

**Storage:**

Store container sealed and in a cool but frost-free place. Keep out of the reach of children.

**Notice:**

For safety-relevant data please see material safety data sheet

**Disposal:**

Only recycle empty containers. Dispose product residues according to EWC –Waste Code no. 07 06 01.

**Available sizes:**

Bottle 250 ml Art. No. 064034074  
 Bottle 1 l Art. No. 064035074  
 Canister 5 l Art. No. 064016074