

Glutogrund TP – White Wallpaper Primer

Solvent-free, white pigmented prime coat for balancing out colour differences in surfaces before wallpapering.

Instructions for use:

Glutogrund TP is ideally suitable for balancing out even extreme colour differences in the surface. It is suitable for all common mineral surfaces as well as gypsum boards, wallpaper and emulsion paints. Especially suited for subsequent wallpapering with translucent or paintable wallpapers as well as for renovation works in which a white background surface is required, e.g. for interior floating and set work.

Glutogrund TP increases the strength of non-firm surfaces and controls the absorbency.

Glutogrund TP is not suitable as a surface for filling compounds containing gypsum or cement.

Technical specifications:

| | |
|----------------------|------------------------------------------------------------------------|
| Components: | Synthetic resin emulsion, titanium dioxide, additives |
| Density: | Approx. 1.5 g/cm ³ |
| pH-value: | 8-9 |
| Consumption: | 100-200 ml/m ² - 10 l suffice for approx. 80 m ² |
| GISBAU Product Code: | M -GP01 |

Surface preparation:

Clean the surface of loose material. Pretreat highly absorbent, sanding and chalking surfaces with *Glutogrund LF Deeply Penetrating Primer*. Remove old wallpapers and distemper paints using *Glutosolv Wallpaper Remover*. Make good cracks and holes using *Glutofill WF Filler for interior use* or *Glutofill WG Super Bonding Filler*.

Application:

Glutogrund TP is ready to use and can be applied using a brush, roller or a suitable spray gun (the max. particle size is 0.2 mm).

Do not apply any further treatment to surfaces to the surface pretreated with *Glutogrund TP* until they have completely dried. The drying time is approx. 6-8 hours, depending on the absorbency of the surface and room ambient conditions.

Do not use if the surface and/or room temperature are below +5° Celsius!
Clean tools in water after use.

Storage:

Store in a cool, but frost-free place! Keep containers tightly sealed!

Important information:

Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

Available size:

PE Cannister 10 l Art. no. 064403074