

## Glutogrund LF Deeply Penetrating Primer

Solvent free hydrosol acrylate primer for indoor and outdoor use.

### Instructions for use:

*Glutogrund LF Deeply Penetrating Primer* is excellently suited for the use as pre-treat of surfaces on all mineral surfaces such as lime, cement and gypsum plaster, sand-lime brick, concrete, aerated concrete, clay bricks and tiles, etc. Especially suitable for priming gypsum boards. Its markedly deep action enables *Glutogrund LF* to firm up sanding, chalking and porous surfaces and reduces their absorbency. *Glutogrund LF* leaves a firm and uniformly absorbent surface for subsequent wallpapering and painting. Not suitable as a primer for plastics, metals and wood.

### Technical specifications:

|                      |   |
|----------------------|---|
| Components:          | Styrene acrylate hydrosol                         |
| Density:             | approx. 1.0 g/cm <sup>3</sup>                     |
| pH-value:            | approx. 7   |
| Usage:               | 50-250 ml/m <sup>2</sup> depending on the surface |
| GISBAU product code: | M-GF01  |

### Application:

*Glutogrund LF Deeply Penetrating Primer* is ready to use and can be applied using a brush or a suitable airless spray gun. Choose the amount to be applied so that no shiny areas result. Prime very absorbent surfaces (e.g. aerated concrete) twice, wet on wet. *Glutogrund LF Deeply Penetrating Primer* can be thinned up to 1:1 with water if it is only to be used to reduce the surface's absorbency.

Consumption of *Glutogrund LF Deeply Penetrating Primer* depends on the surface properties. The amount of ready to use primer required for a single priming coat is approx. 50-100 ml/m<sup>2</sup> for gypsum boards, approx. 100-150 ml/m<sup>2</sup> for gypsum, lime- and cement- based plaster and approx. 150-250 ml/m<sup>2</sup> for aerated concrete.

Protect all elements not to be treated, e.g. by covering, as the *Glutogrund LF* primer is difficult to remove when dry.

Do not use if the surface and/or room temperature is below +5° Celsius!

Clean tools in water immediately after use.

### Storage:

Store cool but frost-free!  
Keep the containers tightly sealed!

### Important information:

Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

### Available sizes:

PE Canister 10 l Art.no. 064303074