

Glutolin T20 Smaragd

Use:

Universal wallpaper adhesive for vinyl, textured, embossed, woodchip and other heavy wallpapers as well as for non-woven wallpapers.

Properties:

- ready to use in 5 minutes
- with polymer adhesion reinforcement

Technical data:

Raw material base:

Bulk density: pH value: starch ether, plastic powder and additives approx. 440 kg/m³ < 11.5

Substrate preparation:

Substrate shall be dry, solid, strong, level, uniformly absorbent and free from adhesion-impairing substances (e.g. mould oil, grease, dust). Remove existing wallpaper. Repair cracks, holes and irregularities with Glutofill WG or Glutofill WF. Pretreat highly absorbent, friable and chalking substrates with Glutogrund LF.

Application:

1. Pour cold water (see table) into clean bucket **2.** Stir water vigorously **3.** Stir pack contents into water **4.** After 5 minutes, thoroughly beat mix and apply

Application to wall covering:

Apply adhesive in required thickness to rear face of wallpaper. After prescribed soaking time, hang wallpaper strips with butted seams, pressing down evenly to remove entrapped air.

Application to substrate:

Dimensionally stable wall coverings that require no softening time can also be applied by wall-pasting method. To do this, apply adhesive generously and uniformly to substrate with short-pile lambskin roller. Place wall covering into adhesive bed and press down evenly to remove entrapped air.

| For | Mixing ratio | |
|-------------|---|--|
| Pre-pasting | 1:40 | |
| | (500 g in 20 ltr water, 1 kg in 40 ltr water) | |
| Heavy | 1:20 | |
| wallpapers | (500 g in 10 ltr water, 1 kg in 20 ltr water) | |
| Lightweight | 1:30 | |
| wallpapers | (500 g in 15 ltr water, 1 kg in 30 ltr water) | |

Observance of wallpaper manufacturer's application guidelines is essential.

Note:

Do not use at building fabric and room temperatures below +5 °C. Immediately wash off adhesive residue with fresh water and rub down with dry cloth. Wash tools with water after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at <u>www.glutolin.de</u> or from <u>sds@glutolin.de</u>.

Storage and disposal:

Store in cool, dry place, out of reach of children. Adhesive residue may be disposed of as domestic waste. Dispose of empty Glutolin packaging as waste paper for recycling.

| Item No. | EAN | Container size |
|-----------|---------------|----------------|
| 022104074 | 4044899221043 | 500 g |
| 022105074 | 4044899221050 | 1 kg |



Glutolin Renovierungsprodukte GmbH, Im Schedetal 1, 34346 Hann. Münden Tel. 05541 / 7003-03, www.glutolin.de

Status: 15.03.2023

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.